



Brick facade everywhere!

vinyBrick brick texture

Decide upon a high insulation.

vinyBrick facade elements provide an excellent energy balance. With appropriate insulation, the rear ventilated facade transforms your house into an energy-efficient house. In addition, another advantage of the robust material made of polyester fiberglass is its lightweight. The elements do not require any maintenance and have a smooth painted surface. For the elements with a sanded stone coating, the so-called „true stone“ effect can even be seen and felt. The elements are available in different colours and decors.



5 YEARS OF
WARRANTY



ENERGY
EFFICIENCY



EASY TO
CLEAN



MADE IN
GERMANY



Technical data

Profile width	430 mm	
Coverage width	410 mm	
Length	1188 mm	
Weight	4,9 kg/m ²	
Density profile	1,7 g/cm ³	EN ISO 10325
Coefficient of linear extension	approx. 0,012 mm/mK	DIN 53752
Tensile strength	≥ 60 MPa	EN ISO 527-4
Flexural modulus	≥ 8000 MPa	EN ISO 14125
Impact strength	≥ 35 KJ/m ²	EN ISO 527-4
Water absorption	≥ 50 mg	ISO 62
Fire behaviour	Class E	DIN EN 13501-1 (= construction material class B2 acc. to DIN 4102-1, normal inflammability)

Assembly

Installation	ordinarily, horizontally on wood substructure
Tools	Woodworking tools
Mounting distance	max. 275 mm
Fixings	Countersunk Head Screw 3 x 40 V2A with torx

Characteristics

Care instructions	Cleaning with commercially available cleaners. No scouring agents.
-------------------	---

